



Product Service

# Attestation of Conformity

No. N8A 17 11 94747 009

**Holder of Certificate:** **Xinsu Global Electronic Co., Limited**  
 Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road  
 Central  
 HONG KONG

**Product:** **Switching power supply unit  
 (SWITCHING POWER SUPPLY/CHARGER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

**Test report no.:** 652101712001

**Date,** 2017-11-23

( Ricky Wang )



**CE** After preparation of the necessary technical documentation as well as the EU conformity declaration the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



**Attestation of Conformity**  
**No. N8A 17 11 94747 009**

**Model(s):**

XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,  
 XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,  
 XSGxxxxy, XSGxxxxyz, XSExxxxy, XSExxxxyz,  
 XSECxxxxy, XSECxxxxyz, XSGxxxxy,  
 XSGxxxxyz, XSExxxxy, XSExxxxyz,  
 XSECxxxxy, XSECxxxxyz  
 (xxx=042-730, which denotes the rated output voltage  
 from 4.2VDC to 73.0VDC; yyyy=0300-9999, which denotes  
 the rated output current from 300mA to 9999mA;  
 yyyyy=10000-11000, which denotes the rated output current  
 from 10000mA to 11000mA; zz=EU or UK, which denotes  
 for marketing purpose and not affect safety, EU=Europe,  
 UK=United Kingdom.)

**Parameters:**

Rated Input :	100-240VAC, 50/60Hz, 3.0A Max
Rated Output :	See page 3 for details
Protection Class :	Class I (For models XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM, XSGxxxxyMM, XSExxxxyMM, XSECxxxxyMM); Class II (For models XSGxxxxy, XSGxxxxyz, XSExxxxy, XSExxxxyz, XSECxxxxy, XSECxxxxyz, XSGxxxxy, XSGxxxxyz, XSExxxxy, XSExxxxyz, XSECxxxxy, XSECxxxxyz)
Degree of Protection :	IP20

**Tested according to:**

EN 60950-1:2006/A2:2013



Product Service

**Attestation of Conformity**  
**No. N8A 17 11 94747 009**

Model No.	Rated output voltage (VDC)	Rated output current (mA)	Max. rated output power (W)
XSGxxxxxyyyyMM,	4.2-9.0	10000	90.0
XSExxxxxyyyyMM,	9.1-14.6	10000-11000	160.6
XSECxxxxxyyyyMM,	14.7-17.0	10000	170.0
XSGxxxxxyyyy, XSGxxxxxyyyyzz, XSExxxxxyyyy, XSExxxxxyyyyzz, XSECxxxxxyyyy, XSECxxxxxyyyyzz	17.1-19.0	10000	190.0
XSGxxxxxyyyyMM,	4.2-9.0	300-9999	90.0
XSExxxxxyyyyMM,	9.1-14.6	300-9999	146.0
XSECxxxxxyyyyMM,	14.7-17.0	300-9999	170.0
XSGxxxxxyyyy, XSGxxxxxyyyyzz, XSExxxxxyyyy, XSExxxxxyyyyzz, XSECxxxxxyyyy, XSECxxxxxyyyyzz	17.1-19.0 19.1-22.0 22.1-32.0 32.1-36.5 36.6-57.9 58.0-58.8 58.9-73.0	300-9999 300-9500 300-8500 300-6000 300-5000 300-3600 300-3400	190.0 190.0 205.8 219.0 210.0 210.2 204.0